

TECHNICAL DATA SHEET

CAG2

CLOROVIV

Creation Date 23/11/18 Rev. 0

GENERAL CHARACTERISTICS		
<p>Fast-dry topcoat that provide high water, alkali*, acids*, mineral oils*, and petrols* resistances. (*max temperature 60°C) Suitable for surfaces exposed to atmospheric agents. Cloroviv can be used in sea environment and is recommended for coat concrete pools. Cloroviv can be identified as finishing coat in fireproof cycles.</p>		
CHEMICAL AND PHYSICAL CHARACTERISTICS		
		NOTE
SPECIFIC WEIGHT	1.25 ± 0,1 Kg/l	
VISCOSITY	R3 1700 cP at T. 20°C	
SOLID CONTENT	65 ± 1% (by weight)	Theoretical
SPREAD RATE : (50 µm secchi)	7,5 m²/Kg	Theoretical
VOC gr/l (Dir. 2010/75/CE)	384.36 gr/l	
AVAILABLE DYES	All dyes available	
BINDER NATURE	Low molecular weight polyolefinic polymer completely chlorinated.	

TECHNOLOGICAL RESISTANCE CHARACTERISTICS	
RESISTANCES	
ATMOSPHERIC AGENTS	Good
NORMAL INDUSTRIAL ENVIRONMENT	Very good
HEAVY INDUSTRIAL ENVIRONMENT	Good
SEA ENVIRONMENT	Very good
HIGH HUMIDITY ENVIRONMENT	Very good
ALTERNATE WATER IMMERSION	Very good
CONTINUOUS FRESH WATER IMMERSION	Good
CONTINUOUS SEA WATER IMMERSION	Very Good
INORGANIC ACIDS	Good
ALKALI	Good
ALCOHOL	Good
ACID SALTS	Good
ALKALINE SALTS	Good



TECHNICAL DATA SHEET

CAG2

CLOROVIV

Creation Date 23/11/18 Rev. 0

APPLICATIONS DATA	
BRUSH	Dil. 5% with our DILUENTE SINTETICO
SPRAY	Dil. 5-10% with our DILUENTE SINTETICO. We raccomand 40-50 microns for coat of paint
DRYING TIMES	
DUST FREE	1 hour
TOUCH FREE	1 hour and 30 minutes
DEEP DRY	24 huors
OVERPAINTABLE	7 hours
Drying times can considerably change according to tamperature and thickness of the paint.	

SURFACE TREATMENT
Surfaces must be accuratly cleaned and free from impurites
ENVIRONMENTAL CONDITIONS
Temperature must be 3 degrees above dew point.
TOOLS CLEANING
Tools can be easily cleaned with our DILUENTE NITRO ANTINEBBIA
STORAGE
In well sealed cans and away from direct sunlight, the product is stable for 12 months

The information given in this sheet and founded on our experience are not intended to be fully exhaustive. Whilst we endeavour to ensure that all advices we give about the product (whether in this sheet or otherwise) are correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. Is supposed that every user liberally opts for the products described on this sheet, after verifying suitability according its requirements. This product is intended for use only by professional applicators in industrial, according the advices described on this sheet, the material safety data sheet and the packaging.