



TECHNICAL DATA SHEET

PC.SEM027

REACTION ACCELERATOR FOR ACRYLIC AND POLYURETHANE PAINTS

Creation date 26/04/2021

Rev. 0

GENERAL INFORMATION		
VIVFAST is an additive for accelerate the reticulation of polyurethane and acrylic system.		
FINAL CHARACTERISTICS		
		MESURE UNIT
SPECIFIC WEIGHT	0.9 ± 0,1	Kg/L
COLOR	Transparent	Eye control
ASPECT	Transparent without impurities in suspension	Eye control
ISTRUCTIONS FOR USE		
Add 0.5-1% of VIVFAST to your paint (calculated on PART A) before addition of the hardener, mix homogeneously and then add the hardener.		
WARNINGS		
The use of this additive reduce the pot life of the product. An over quantity of VIVFAST can inflict negatively on distension and brightness of the paint.		

STORAGE
In fresh and not highly humidity environments VIVFAST lasts, at least, 12 months.

The information given in this sheet and founded on our experience are not intended to be fully exhaustive. Whilst we endeavour to ensure that all advices we give about the product (whether in this sheet or otherwise) are correct, we have no control over either the quality or condition of the substrate or the many factors affecting the use and application of the product. It is supposed that every user liberally opts for the products described on this sheet, after verifying suitability according its requirements. This product is intended for use only by professional applicators in industrial, according the advices described on this sheet, the material safety data sheet and the packaging.