

TECHNICAL DATA SHEET SANVIV

Creation date 06/05/2022
Rev. 0

GENERAL INFORMATION		
Fungicide sterilising paint for exterior and interior walls. Sterilises walls from all kinds of mould and fungi.		
FINAL CHARACTERISTICS		
		NOTES
SPECIFIC WEIGHT	0,95 ± 0,1 Kg/L	
VISCOSITY		Not available
SOLID CONTENT		Not available
YIELD (50 dry µm)		Not available
CATALYSIS	Not requested	
AVAILABLE COLOURS	Transparent	

RESISTANCE AND TECHNOLOGICAL CHARACTERISTICS	
APPLICATION	
BRUSH/ROLLER	Ready to use
APPLICATION	Brush off the areas of the wall most attacked by mould, then apply a coat of SANIVIV. During application of the paint, it is advisable to wear gloves and goggles. To complete the cycle and to obtain a long-lasting result, it is advisable to apply a subsequent coat of VIV ANTIMOULD after 24 hours.

OVERPAINT
This product is overpaintable after 24 hours
ENVIRONMENTAL CONDITION
Substrate and external temperature must be at least 3 degrees above the dew point
TOOLS CLEANING
Tools can be clean with WATER
STORAGE
In a cool, low humidity place and in a well-sealed tin, the product is stable for at least 12 months. The storage temperature should be between 5°C and 35°C.

The information on this data sheet is indicative and based on our knowledge derived from experience and testing and can in no way constitute a guarantee. The buyer/user independently decides on the suitability of the product for his or her own needs in the context of the specific field of application. Please refer to the relevant toxicological data sheet for safety information.