

TECHNICAL DATA SHEET VIVWASH

Creation date 14/03/21
Latest update 22/04/25
Rev. 1

GENERAL INFORMATION		
Universal matt, washable and breathable water-based paint with excellent whiteness, good coverage and resistance to washing. Easy to apply, it evens out the surface, masking small imperfections thanks to its high opacity. Ideal for ceilings and interiors. Low emission		
TECHNICAL INFORMATIONS		
		NOTE
YIELD (50 dry μm)	10-12 m^2/L	Theoretical
AVAILABLE DYES	White, colours on request	

TECHNOLOGICAL INFORMATIONS	
APPLICATIONS MODALITY	
BRUSH, ROLLER	Dil. 20-30% with DEMINERALIZED WATER
PAINTED WALLS	Brush off any residues of previous processes, dust and impurities. On absorbent supports, use a coat of VIVFIX beforehand. Proceed with the application of 2 or more coats of water-based paint, respecting application times, keeping the first coat of paint slightly (5%) thinner

DRYING	
DUST FREE	n/a
TOUCH FREE	30 min
DEEP DRYING	24 hours
Drying times can vary significantly depending on the thickness applied.	

TECHNICAL DATA SHEET VIVWASH

Creation date 14/03/21
Latest update 22/04/25
Rev. 1

OVERCOATING
The product can be overpainted after 4-6 hours
ENVIRONMENTAL CONDITION
The substrate and outdoor temperature must be at least 3 degrees above the dew point.
TOOLS CLEANING
Tools can be cleaned of undried product with DEMINERALISED WATER.
STORAGE
In a cool and dry place, and in well sealed tin, the product is stable for at least 12 months. Storage temperature should be between 5°C and 35°C

The information given in this data sheet is indicative and based on our knowledge derived from experience and testing and can in no way constitute a guarantee. The purchaser/user is responsible for determining the suitability of the product for his or her own requirements in the context of the specific field of application. Please refer to the relevant toxicological data sheet for safety information.